

KXTE: Die Cast Aluminum LED Exit Sign

Project:	
Type:	
Catalog #:	



Features

- Energy efficient LED technology
- Spec-grade curved faceplate
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

Electrical

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- Maintenance-free, rechargeable Ni-Cad battery (EM model)
- Internal solid-state transfer switch automatically connects the internal battery to LEDs for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting

- Die cast mounting canopy included (provides top, end or back mount convenience)
- Universal wall mounting K/O pattern

Housing

- Premium-grade, extruded aluminum housing (also available in black or white powder coated)
- Easily removable chevron directional indicators
- Unique design allows double face conversion in the field
- Quick-snap face plate closure

Illumination

- Ultra-bright, energy efficient, long-lasting Red or Green LED

Options

- SDT: Self-Diagnostic (option SDT) continually diagnoses unit's performance and tests system (auto battery discharge once every 30 days and once every 12 months) to ensure reliable operation and to meet electrical and life safety codes
- 2C: Dual Circuit option on the AC-only unit enables it to be connected to two different (primary and secondary, one acting as a back-up for the other) supplies at the same time (contact customer service for more information)
- TP: Screws in corners seal the unit, preventing access to unauthorized personnel
- Die-Cast EXIT panels available to order separately (contact customer service)



KXTEU1RWW



KXTEU1GBB



KXTEU1RBA




Specify option "TP" for Tamper-Proof face plates

Warranty

- Five Year Warranty on all electronics and housing. Batteries are prorated warranted for 5 years.

Dimensions



ORDERING INFORMATION

Model	Face #	Letter Color	Housing Color	Face Color	Battery	Options
KXTE	1 - Single Face	R - Red	A - Brushed Aluminum	A - Brushed Aluminum	Blank - AC Only	SDT - Self Diagnostics
	2 - Double Face	G - Green	B - Black Powder Coated	B - Black Powder Coated	EM - NiCad Battery	2C - 2 Circuit Operation
	3 - Universal Single/Double		W - White Powder Coated	W - White Powder Coated		FP - Face Plate (order separately) TP - Tamper Proof Screws

Model	Face #	Letter Color	Panel Color	Housing Color	Battery	Options
-	-	-	-	-	-	-

