# ELXTE: LED Edgelit Exit Sign-Surface Mount

Project:	
Туре:	
Catalog #:	

#### Features

- Energy efficient LED technology
- Decals & template provided for chevron directional indicators
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

## Electrical

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- Maintenance-free, rechargeable Ni-Cad battery (EM model)
- Internal solid-state transfer switch automatically connects the internal battery to LED Board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

## Mounting

Die-cast aluminum mounting canopy included—provides top, end or back mount convenience

#### Housing

• Premium-grade, extruded aluminum housing (also available in black or white powder coated)

#### **Options**

- SDT: Self-Diagnostic (option SDT) continually diagnoses unit's performance and tests system (auto battery discharge once every 30 days and once every 12 months) to ensure reliable operation and to meet electrical and life safety codes
- DC: Dual Circuit option on the AC-only unit enables it to be connected to two different (primary and secondary, one acting as a back-up for the other) supplies at the same time (consult factory for more information on this)
- Edgelit EXIT panels available to order separately (contact customer service)
- Double face utilizes a silver or white mylar insert

# **ORDERING INFORMATION**







Wall mount

Side mount


#### Illumination

- Ultra-bright, energy efficient, long-lasting Red or Green LED
- UV-stabilized ultra-clear acrylic edgelit panel provided consistent, uniform illumination

#### Warranty

• Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.

#### Dimensions







Special Wording



Model	Face #	Letter Color	Panel Color	<b>Housing Color</b>	Battery	Options
ELXTE	1 - Single Face	R - Red	C - Clear	W - White	Blank - AC Only	SDT - Self Diagnostics
	2 - Double Face	G - Green	M - Mirror (Silver Mylar)	B - Black	EM - NiCad Battery	2C - Dual Circuit
			W - White (White Mylar)	A - Anodized Aluminum		SW - Special Wording

Model	Face #	Letter Color	Panel Color	Housing Color	Battery	Options
			_			

