

# EZXTE: LED Exit Sign

<b>Project:</b>	
<b>Type:</b>	
<b>Catalog #:</b>	

## Features

- Compact, low-profile design in neutral finish
- Energy-efficient LED technology
- EZ snap-out chevron directional indicators
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

## Electrical

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- Long-life, maintenance-free, rechargeable NiCd battery (EM model)
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

## Mounting

- Universal surface mount, wall or ceiling, with EZ-snap thermoplastic mounting canopy, which snaps into place making installation quick & easy.

## Housing

- Injection-molded, engineering-grade, V-0 flame retardant, high-impact, thermoplastic in white or black finish

## Options

- SDT: Self-Diagnostic (option SDT) continually diagnoses unit's performance and tests system (auto battery discharge once every 30 days and once every 12 months) to ensure reliable operation and to meet electrical and life safety codes
- DC: Dual Circuit option on the AC-only unit enables it to be connected to two different (primary and secondary, one acting as a back-up for the other) supplies at the same time (contact customer service).



## Illumination

- Ultra-bright, energy efficient, long-life Red or Green LED



SALIDA faceplates also available.

## Warranty

- Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.

## Dimensions



Special Wording Sign samples

## ORDERING INFORMATION

Model	Face #	Letter Color	Housing Color	Battery	Options
EZXTE	U2 - Universal Single/Double	R - Red G - Green	W - White B - Black	Blank - AC Only EM - NiCad Battery	SDT - Self Diagnostics 2C - 2 Circuit Operation (ONLY 1 HOT CIRCUIT AT A TIME) SW - Special Wording

Model	Face #	Letter Color	Housing Color	Battery	Options
-	-	-	-	-	-

