RMR-16WP: Wet Location Emergency Light with MR-16 Halogen Lamp Heads

| Project: | |
|------------|--|
| Туре: | |
| Catalog #: | |

Features

- Compact, low-profile design in neutral finish
- Fully-gasketed polycarbonate enclosure provides resistance to corrosive atmospheres and non-hazardous environments
- UL listed for wet locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

Electrical

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- 6V, 4.5Ah, sealed lead acid, maintenance-free, rechargeable battery
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours

Mounting

Surface mount via easy connect back plate

Housing

- Injection-molded, engineering-grade, V-0 flame retardant, high-impact, thermoplastic in neutral gray finish
- Fully-gasketed clear polycarbonate cover offers protection against wet, nonhazardous dust, and hose-down locations



Illumination

• Two adjustable, ultra-bright, round 6V, 7W MR-16 halogen lighting heads

Options


• Using the optional internal heater (-HTR) enables the unit to be used in cold environments (contact customer service).

Warranty

• Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.

Dimensions

4.2 14.9"



ORDERING INFORMATION

| Model | Color | Options |
|----------|----------|-----------------------|
| RMR-16WP | G - Gray | HTR - Internal Heater |

| Model | Color | Options | | |
|-------|---------|---------|--|--|
| | - | - | | |
| | oboc | TM | | |
| | LIGHTIN | N G | | |