

LED Center-Basket AL-MB-Series



Features

- Center Basket with latest LED technology
- Clean appearance with no exposed fasteners
- 0-10V dimmable driver
- Modern shallow design, easy installation

Model Name	AL-MB-2X4-48-8-40-RDICB
Mi Item #	06786460*
Power Consumption	48 watt
Luminous Efficacy	80 lm/W
Luminous Flux	3,840 lm
Color Temperature	4000K, 5000K
Color Rendering	> 80 CRI
Life Time Rating	50,000 Hours
Input Voltage	120 - 277V AC
Size (W x L x H)	24" x 48" x 3"
Options	0-10V Dimming (Standard)

Applications

- Drop/Grid Ceiling
- Retail Stores
- Schools
- Hospitals
- Laboratories

*Mi Numbers are for 4000K models unless otherwise specified.

Specifications are subject to change with or without notice.



LED Office Lighting



Call. 800-526-9328
Click. www.MotionIndustries.com
Visit. Over 550 Locations



LED Panels AL-SP Series



Features

- Ultra thin LED panel light
- Environmentally friendly with no mercury
- Replaces 2' x 2' and 2' x 4' troffers
- 0-10v dimming standard
- High lumen efficiency and CRI

Model Name	AL-SP-2X2	AL-SP-2X4
Mi Item #	06786625*	06786629*
Power Consumption	40 watt	50 watt
Luminous Efficacy	115 lm/W	120 lm/w
Luminous Flux	4,600/4670 lm	5990/6130 lm
Color Temperature	4000K/5000K	
Color Rendering	> 80 CRI	
Life Time Rating	50,000 Hours	
Input Voltage	120 - 277V AC	
Size (W x L x H)	23.6" x 23.6" x 0.4"	47.2" x 47.2" x 0.4"
Options	Dimmable Model Available	



Call. 800-526-9328
 Click. www.MotionIndustries.com
 Visit. Over 550 Locations



LED Wraps AL-SP-LW Series



Features

- Integrated LED module wrap fixture
- Housing: Die-formed cold-rolled steel
- Acrylic prismatic diffuser
- Diffuser hinges open from both sides
- Excellent lumen efficiency and high CRI

Model Name	AL-SP-LW
Mi Item #	07240694*
Power Consumption	36 watt
Luminous Efficacy	105 lm/W
Luminous Flux	3,780 lm
Color Temperature	4000K/5000K
Color Rendering	> 80 CRI
Life Time Rating	50,000 Hours
Input Voltage	120 - 277V AC
Size (W x L x H)	49.5" x 8.8" 2.5"