

LED Emergency Light AL-LED-R1



Mi Item # 05563767



Features

- Adjustable LED lamp heads provides optimal center-to-center spacing.
- 1 watt (8 LEDs x 0.125 watt) per head.
- Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

Steel Exit Light AL-LED-SXTEU



Mi Item # 07179198



Features

- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Durable, powder-coated 20-gauge steel construction in white or black finish.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

All LED Exit and Emergency Combo AL-LED-CLPU



Mi Item # 06786605



Features

- 4.5W (36 LEDs x 0.125 watts) per light pipe.
- Adjustable high-performance, smooth, chrome-plated, metallized reflector and acrylic, UV-stabilized "light pipe" lens for optimal light distribution.
- Ultra-bright, energy efficient, long-life Red or Green LED exit sign illumination.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finishes.
- Remote capable standard.

Specifications are subject to change with or without notice.

LED Exit and Emergency Lighting



abacoTM
LIGHTING



LED Exit Sign AL-LED-EZXTE



Mi Item # 06786616



Features

- 4.8V long life, maintenance-free, rechargeable NiCd battery.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- Ultra-bright, energy efficient, long-life Red or Green LED exit sign illumination.

AL-LED-WLEZXTE



Mi Item # 07179219



Features

- Ultra-bright, energy efficient, long-life Red or Green LED exit sign illumination.
- Corrosion-resistant enclosure with engineering grade silicone gasket.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).

LED Emergency Light AL-LED-SDXR627



Mi Item # 05214318



Features

- Two, 6V, 1.0W adjustable square LED lamp heads in engineering grade, high-impact resistant, thermoplastic.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Runs up to 8 hours without remote heads.

AL-LED-TFX-2



Mi Item # 06786595



Features

- Resistant to corrosive atmospheres, non-hazardous dust environments, water spray and splashing water.
- 1.875W (15 LEDs x 0.125) per head.

All LED Exit and Emergency Combo AL-LED-CXTE



Mi Item # 06786608



Features

- 1 watt (8 LEDs x 0.125 watt) per head.
- 9.6V Long-life, maintenance-free, rechargeable NiCd battery.
- Adjustable LED lamp heads provides optimal center-to-center spacing.

AL-LED-CWLEZXTEU



Mi Item # 06786441



Features

- Corrosion-resistant enclosure engineering grade silicone gasket.
- 3.6W (3 LEDs x 1.2 watt) per head.
- Optional, Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.