

LED Center-Basket AL-MB-Series



Features

- Center Basket with latest LED technology
- Clean appearance with no exposed fasteners
- 0-10V dimmable driver
- Modern shallow design, easy installation

| Model Name | AL-MB-2X4-48-8-40-RDICB |
|-------------------|--------------------------|
| Mi Item # | 06786460* |
| Power Consumption | 48 watt |
| Luminous Efficacy | 80 lm/W |
| Luminous Flux | 3,840 lm |
| Color Temperature | 4000K, 5000K |
| Color Rendering | > 80 CRI |
| Life Time Rating | 50,000 Hours |
| Input Voltage | 120 - 277V AC |
| Size (W x L x H) | 24" x 48" x 3" |
| Options | 0-10V Dimming (Standard) |

Applications

- Drop/Grid Ceiling
- Retail Stores
- Schools
- Hospitals
- Laboratories

*Mi Numbers are for 4000K models unless otherwise specified.

Specifications are subject to change with or without notice.

LED Office Lighting



LED Panels AL-SP Series



Features

- Ultra thin LED panel light
- Environmentally friendly with no mercury
- Replaces 2' x 2' and 2' x 4' troffers
- 0-10v dimming standard
- High lumen efficiency and CRI

| Model Name | AL-SP-2X2 | AL-SP-2X4 |
|-------------------|--------------------------|----------------------|
| Mi Item # | 06786625* | 06786629* |
| Power Consumption | 40 watt | 50 watt |
| Luminous Efficacy | 115 lm/W | 120 lm/w |
| Luminous Flux | 4,600/4670 lm | 5990/6130 lm |
| Color Temperature | 4000K/5000K | |
| Color Rendering | > 80 CRI | |
| Life Time Rating | 50,000 Hours | |
| Input Voltage | 120 - 277V AC | |
| Size (W x L x H) | 23.6" x 23.6" x 0.4" | 47.2" x 47.2" x 0.4" |
| Options | Dimmable Model Available | |



LED Wraps AL-SP-LW Series



Features

- Integrated LED module wrap fixture
- Housing: Die-formed cold-rolled steel
- Acrylic prismatic diffuser
- Diffuser hinges open from both sides
- Excellent lumen efficiency and high CRI

| Model Name | AL-SP-LW |
|-------------------|-------------------|
| Mi Item # | 07240694* |
| Power Consumption | 36 watt |
| Luminous Efficacy | 105 lm/W |
| Luminous Flux | 3,780 lm |
| Color Temperature | 4000K/5000K |
| Color Rendering | > 80 CRI |
| Life Time Rating | 50,000 Hours |
| Input Voltage | 120 - 277V AC |
| Size (W x L x H) | 49.5" x 8.8" 2.5" |