







Dimensional Drawing



MOUNTING OPTIONS



Specifications

Model Name	HBVT3-14	HBVT3-21	HBVT3-28	HBVT3-34
Input Wattage (W)	102W	150 W	200W	241W
Voltage (V)	U (120-277V)			
Lumen Output (lm)	14,864 lm	21,406 lm	28,948 lm	34,240 lm
Efficacy (lm/W)	140 lm/W	139 lm/W	137 lm/W	
Color Rendering Index	80+ CRI			
Color Temperature	40 (4000K) / 50 (5000K)			
Dimming Compatible	0-10vdc			
Replacement Wattage	250-400W HID, 4LT5, 6LT8	400W HID, 4LT5, 6LT8	400 HID, 6LT5	400-750W HID, 8LT5
Longevity (L70)	174,000 Hours			
Size (ØD x H)	11.7" x 7.3"		14.2" x 8.5"	
Weight	6.8 lbs		11.2 lbs	
Ambient Temperature	-40° F to 131° F			

Ideal for wet location areas, food processing, warehouse, manufacturing, and cold environments.

FEATURES

- Excellent uniform light distribution
- Durable cast aluminum body with rugged design
- Long-life LEDs provide 174,000 hours of operation with at least 70% of initial lumen output (L70)
- No hazardous material, mercury or sodium
- IP65 Rated
- Watertight, compression-type electrical connectors prevent moisture intrusion
- 5-year limited warranty
- Glass Lens

Ordering Guide

EG: AL-BE-HBVT3-14-8-40-U-Y

Model Name	Wattage	CRI	CCT	Driver	Options
AL-BE-HBVT3	14: 14,864 lm 21: 21,406 lm 28: 28,948 lm 34: 34,240 lm	8: >80	40: 4000k 50: 5000k	U: Universal 120-277V	Y: Yoke Mount SH: Snap Hook