

DESCRIPTION

Tempered glass lens resists breakage and reduces replacement and maintenance costs. Optional 40" swing arm with 1.5" square tubing for extra strength.

FEATURES

- IP67 rated for dust and water resistance.
- 180° swivel bracket on light head allows unlimited mounting options
- 88 lumens per watt
- Color Rendering Index (CRI) > 70
- 16 ft. oil-resistant power cord remains flexible in cold weather
- Input Voltage Range: 120V AC
- CSA outdoor certificate
- Five (5) year warranty



SPECIFICATIONS

Arm Extension

AL-LDL-16W-ARM



AL-LDL-16W

Power Consumption	16 watt
Input Voltage	120 - 277V
Lumen Output	1,400 Lm
Efficacy	87 Lm/W
Color Rendering	> 80 CRI
Color Temperature	5000K
Warranty	5 Years
Life Time Rating	50,000 hrs
Weight	8lbs
Lens	Tempered Glass
Body	Die-cast Aluminum
Operating Temp.	-22°F ~ 113°F (-30°C ~ 45°C)

ORDERING GUIDE

Series

AL-LDL-16W
AL-LDL-16W-ARM

Applications

- Tractor trailers up to 53' for loading and unloading
- Manufacturing facilities
- Warehouse facilities
- Industrial facilities
- Loading docks
- Under awnings
- Cold storage
- Landscape
- Signage